


<b>Luminaire Photometric Performance</b> <i>Typical</i>	Luminous Flux	6045 lm
	Luminous Efficacy	155 lm/W
	CCT	3000 K
	R <sub>a</sub>	> 80
	SDCM	3 step
<b>Electrical Characteristics</b>	Power Consumption	39 W
	Input Voltage	220 - 240 V
	Operating Frequency	0/50 - 60 Hz
	Power Factor	> 0,96
	Total Harmonic Distortion	≤ 10 %
	Dimming	Casambi
<b>Physical Characteristics</b>	Weight	1,9 kg
	Size (L x W x H)	1632 x 44 x 48 mm
	Ingress & Impact Protection	IP20; IK8
	Operating Temperature	-20 ~ 40 °C
	Installation	Quick Bracket
<b>Material Characteristics</b>	Lens	PMMA
	Body	Aluminium
	Wiring	Halogen-free
<b>Luminaire Life Time</b>	L <sub>70B50</sub>	100 000 h
	C <sub>10</sub>	60 000 h
<b>Warranty</b>		5 years

Light Distribution



MCB Loadin Information

MCB Type	Rating	Quantity of luminaires
Type B	10 A	19 per MCB
	16 A	31 per MCB
	20 A	39 per MCB
Type C *	10 A	32 per MCB
	16 A	53 per MCB
	20A	66 per MCB

\* Recommended