


Luminaire Photometric Performance <i>Typical</i>	Luminous Flux	8060 lm
	Luminous Efficacy	155 lm/W
	CCT	3000 K
	R _a	> 80
	SDCM	3 step
Electrical Characteristics	Power Consumption	52 W
	Input Voltage	220 - 240 V
	Operating Frequency	0/50 - 60 Hz
	Power Factor	> 0,96
	Total Harmonic Distortion	≤ 10 %
	Dimming	Casambi
Physical Characteristics	Weight	1,9 kg
	Size (L x W x H)	1632 x 44 x 48 mm
	Ingress & Impact Protection	IP20; IK8
	Operating Temperature	-20 ~ 40 °C
	Installation	Quick Bracket
Material Characteristics	Lens	PMMA
	Body	Aluminium
	Wiring	Halogen-free
Luminaire Life Time	L ₇₀ B ₅₀	100 000 h
	C ₁₀	60 000 h
Warranty		5 years

Light Distribution



MCB Loadin Information

MCB Type	Rating	Quantity of luminaires
Type B	10 A	11 per MCB
	16 A	18 per MCB
	20 A	22 per MCB
Type C *	10 A	18 per MCB
	16 A	30 per MCB
	20A	37 per MCB

* Recommended