


**Luminaire Photometric Performance**

*Typical*




Luminous Flux	10075 lm
Luminous Efficacy	155 lm/W
CCT	4000 K
R <sub>a</sub>	> 80
SDCM	3 step

**Electrical Characteristics**




Power Consumption	65 W
Input Voltage	220 - 240 V
Operating Frequency	0/50 - 60 Hz
Power Factor	> 0,96
Total Harmonic Distortion	≤ 10 %
Dimming	DALI

**Physical Characteristics**




Weight	2,7 kg
Size (L x W x H)	2282 x 44 x 48 mm
Ingress & Impact Protection	IP20; IK8
Operating Temperature	-20 ~ 40 °C
Installation	Quick Bracket

**Material Characteristics**



Lens	PMMA
Body	Aluminium
Wiring	Halogen-free

**Luminaire Life Time**




L <sub>70B50</sub>	100 000 h
C <sub>10</sub>	60 000 h

**Warranty**

5 years

**Light Distribution**



**MCB Loadin Information**

MCB Type	Rating	Quantity of Luminaires	
Type B	10 A	11	per MCB
	16 A	18	per MCB
	20 A	22	per MCB
Type C *	10 A	18	per MCB
	16 A	30	per MCB
	20A	37	per MCB

\* Recommended